

(12) **United States Patent**
Shachar et al.

(10) **Patent No.:** **US 9,655,539 B2**
(45) **Date of Patent:** **May 23, 2017**

(54) **SYSTEM AND METHOD FOR TARGETING CATHETER ELECTRODES**

(75) Inventors: **Yehoshua Shachar**, Santa Monica, CA (US); **Bruce Marx**, Ojai, CA (US); **David Johnson**, West Hollywood, CA (US); **Leslie Farkas**, Ojai, CA (US); **Steven Kim**, New York, NY (US)

(73) Assignee: **Magnetecs, Inc.**, Inglewood, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 1218 days.

(21) Appl. No.: **13/450,831**

(22) Filed: **Apr. 19, 2012**

(65) **Prior Publication Data**

US 2012/0296200 A1 Nov. 22, 2012

Related U.S. Application Data

(63) Continuation of application No. 12/615,176, filed on Nov. 9, 2009, now abandoned.

(51) **Int. Cl.**

A61M 25/095 (2006.01)
A61B 5/042 (2006.01)
A61B 34/00 (2016.01)
A61B 18/14 (2006.01)
A61B 18/00 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 5/042** (2013.01); **A61B 34/70** (2016.02); **A61B 34/73** (2016.02); **A61B 18/1492** (2013.01); **A61B 2018/00577** (2013.01); **A61B 2018/00839** (2013.01); **A61B 2562/0209** (2013.01); **A61B 2562/043** (2013.01)

(58) **Field of Classification Search**

CPC **A61B 5/042**; **A61B 18/1492**; **A61B 34/70-34/77**; **A61B 2018/00577**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,043,309 A 9/1959 McCarthy
3,358,676 A 12/1967 Frei et al.
3,622,869 A 11/1971 Golay
3,628,527 A 12/1971 West
(Continued)

FOREIGN PATENT DOCUMENTS

DE 102005045073 A1 3/2007
EP 0 147 082 A2 7/1985
(Continued)

OTHER PUBLICATIONS

Ernst et al, Initial Experience With Remote Catheter Ablation Using a Novel Magnetic Navigation System Magnetic Remote Catheter Ablation, *Circulation*. 2004;109:1472-1475.*



(Continued)

Primary Examiner — Serkan Akar

(57) **ABSTRACT**

A system and method is described for a catheter guidance system which allows an operator to use a mapping catheter to specify tissue target locations for the automatic guidance of a second therapeutic catheter. The operator places a mapping catheter at a desired location, and commands the catheter guidance system by either selecting a point on that catheter or one of the catheter electrode electrocardiograms. The operator may target the selected dynamic location, or tissue contact beyond that location on a specific side of the mapping catheter.

4 Claims, 4 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

3,746,937	A	7/1973	Koike	6,104,944	A	8/2000	Martinelli
3,961,632	A	6/1976	Moossun	6,122,538	A	9/2000	Sliwa, Jr. et al.
4,063,561	A	12/1977	McKenna	6,128,174	A	10/2000	Ritter et al.
4,071,042	A	1/1978	Lombard et al.	6,129,668	A	10/2000	Haynor et al.
4,096,862	A	6/1978	DeLuca	6,148,823	A	11/2000	Hastings
4,162,679	A	7/1979	Reenstierna	6,152,933	A	11/2000	Werp et al.
4,173,228	A	11/1979	Van Steenwyk et al.	6,157,853	A	12/2000	Blume et al.
4,244,362	A	1/1981	Anderson	6,200,312	B1	3/2001	Zikorous et al.
4,249,536	A	2/1981	Vega	6,216,027	B1	4/2001	Willis et al.
4,270,252	A	6/1981	Harrison et al.	6,233,476	B1	5/2001	Strommer et al.
4,292,961	A	10/1981	Kawashima	6,241,671	B1	6/2001	Ritter et al.
4,354,501	A	10/1982	Colley et al.	6,292,678	B1	9/2001	Hall et al.
4,392,634	A	7/1983	Kita	6,295,466	B1	9/2001	Ishikawa et al.
4,671,287	A	6/1987	Fiddian-Green	6,296,604	B1	10/2001	Garibaldi et al.
4,727,344	A	2/1988	Koga et al.	6,298,257	B1	10/2001	Hall et al.
4,735,211	A	4/1988	Takasugi	6,304,768	B1	10/2001	Blume et al.
4,809,713	A	3/1989	Grayzel	6,311,082	B1	10/2001	Creighton, IV et al.
4,860,744	A	8/1989	Johnson et al.	6,314,312	B1	11/2001	Wessels et al.
4,869,247	A	9/1989	Howard, III et al.	6,315,709	B1	11/2001	Garibaldi et al.
4,870,306	A	9/1989	Petersen	6,330,467	B1	12/2001	Creighton, IV et al.
4,943,770	A	7/1990	Ashley-Rollman et al.	6,352,363	B1	3/2002	Munger et al.
4,984,581	A	1/1991	Stice	6,364,823	B1	4/2002	Garibaldi et al.
4,985,015	A	1/1991	Obermann et al.	6,375,606	B1	4/2002	Garibaldi et al.
5,031,634	A	7/1991	Simon	6,381,485	B1	4/2002	Hunter et al.
5,063,935	A	11/1991	Gambale	6,385,472	B1	5/2002	Hall et al.
5,083,562	A	1/1992	de Coriolis et al.	6,401,723	B1	6/2002	Garibaldi et al.
5,090,956	A	2/1992	McCoy	6,428,551	B1	8/2002	Hall et al.
5,125,888	A	6/1992	Howard et al.	6,454,776	B1	9/2002	Tajjima et al.
5,167,626	A	12/1992	Casper et al.	6,459,924	B1	10/2002	Creighton, IV et al.
5,209,234	A	5/1993	LaRocca	6,459,926	B1	10/2002	Nowlin et al.
5,226,847	A	7/1993	Thomas et al.	6,475,223	B1	11/2002	Werp et al.
5,249,163	A	9/1993	Erickson	6,490,474	B1	12/2002	Willis et al.
5,255,680	A	10/1993	Darrow et al.	6,505,062	B1	1/2003	Ritter et al.
5,257,636	A	11/1993	White	6,507,751	B2	1/2003	Blume et al.
5,269,759	A	12/1993	Hernandez et al.	6,522,909	B1	2/2003	Garibaldi et al.
5,353,807	A	10/1994	DeMarco	6,524,303	B1	2/2003	Garibaldi
5,377,678	A	1/1995	Dumoulin et al.	6,529,761	B2	3/2003	Creighton, IV et al.
5,396,902	A	3/1995	Brennen et al.	6,537,196	B1	3/2003	Creighton, IV et al.
5,421,338	A	6/1995	Crowley et al.	6,562,019	B1	5/2003	Sell
5,462,054	A	10/1995	Rapoport et al.	6,575,977	B1	6/2003	Michelson
5,485,748	A	1/1996	Zeamer	6,582,429	B2	6/2003	Krishnan et al.
5,492,131	A	2/1996	Galel	6,587,709	B2	7/2003	Solf et al.
5,546,948	A	8/1996	Hamm et al.	6,594,517	B1	7/2003	Nevo
5,550,469	A	8/1996	Tanabe et al.	6,630,879	B1	10/2003	Creighton, IV et al.
5,558,091	A	9/1996	Acker et al.	6,662,034	B2	12/2003	Segner et al.
5,573,012	A	11/1996	McEwan	6,667,660	B2	12/2003	Schrodinger et al.
5,588,442	A	12/1996	Scovil et al.	6,669,693	B2	12/2003	Friedman
5,624,430	A	4/1997	Eton et al.	6,677,752	B1	1/2004	Creighton, IV et al.
5,645,065	A	7/1997	Shapiro et al.	6,692,492	B2	2/2004	Simpson et al.
5,650,725	A	7/1997	Powell et al.	6,702,804	B1	3/2004	Ritter et al.
5,654,864	A	8/1997	Ritter et al.	6,704,694	B1	3/2004	Basdogan et al.
5,656,030	A	8/1997	Hunjan et al.	6,714,901	B1	3/2004	Cotin et al.
5,681,260	A	10/1997	Ueda et al.	6,726,675	B1	4/2004	Beyar
5,683,384	A	11/1997	Gough et al.	6,733,511	B2	5/2004	Hall et al.
5,702,420	A	12/1997	Sterling et al.	6,740,103	B2	5/2004	Hall et al.
5,702,433	A	12/1997	Taylor et al.	6,752,767	B2	6/2004	Turovskly et al.
5,704,897	A	1/1998	Truppe	6,755,816	B2	6/2004	Ritter et al.
5,709,661	A	1/1998	Van Egmond et al.	6,757,557	B1	6/2004	Bladen et al.
5,711,299	A	1/1998	Manwaring et al.	6,771,996	B2	8/2004	Bowe et al.
5,769,843	A	6/1998	Abela et al.	6,776,165	B2	8/2004	Jin
5,775,322	A	7/1998	Silverstein et al.	6,786,219	B2	9/2004	Garibaldi et al.
5,779,694	A	7/1998	Howard et al.	6,817,364	B2	11/2004	Garibaldi et al.
5,808,665	A	9/1998	Green	6,833,814	B2	12/2004	Gilboa et al.
5,821,920	A	10/1998	Rosenberg et al.	6,834,201	B2	12/2004	Gillies et al.
5,843,153	A	12/1998	Johnston et al.	6,853,965	B2	2/2005	Massie et al.
5,844,140	A	12/1998	Seale	6,902,528	B1	6/2005	Garibaldi et al.
5,851,185	A	12/1998	Berns	6,914,552	B1	7/2005	McEwan
5,904,691	A	5/1999	Barnett et al.	6,950,689	B1	9/2005	Willis et al.
5,919,135	A	7/1999	Lemuelson	6,960,847	B2	11/2005	Suzuki et al.
5,931,818	A	8/1999	Werp et al.	6,961,632	B2	11/2005	Hashimoto et al.
5,971,976	A	10/1999	Wang et al.	6,970,733	B2	11/2005	Willis et al.
6,014,580	A	1/2000	Blume et al.	7,280,863	B2	10/2007	Shachar
6,015,414	A	1/2000	Werp et al.	7,282,034	B2	10/2007	Burbank et al.
6,038,488	A	3/2000	Barnes et al.	7,316,700	B2	1/2008	Alden et al.
6,073,043	A	6/2000	Schneider	7,341,063	B2	3/2008	Garibaldi et al.
				7,346,379	B2	3/2008	Eng et al.
				7,468,042	B2	12/2008	Turovskly et al.
				7,495,537	B2	2/2009	Tunay
				7,543,239	B2	6/2009	Viswanathan et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

7,660,023 B2 2/2010 Hunter et al.
 7,725,157 B2 5/2010 Dumoulin et al.
 7,751,867 B2 7/2010 Viswanathan
 7,769,427 B2 8/2010 Shachar
 7,840,253 B2 11/2010 Tremblay et al.
 7,850,642 B2 12/2010 Moll et al.
 7,869,854 B2 1/2011 Shachar et al.
 7,873,402 B2 1/2011 Shachar
 7,963,288 B2 6/2011 Rosenberg et al.
 7,972,298 B2 7/2011 Wallace et al.
 7,974,681 B2 7/2011 Wallace et al.
 8,000,773 B2 8/2011 Rouso et al.
 8,027,714 B2 9/2011 Shachar
 8,041,413 B2 10/2011 Barbagli et al.
 8,052,636 B2 11/2011 Moll et al.
 2001/0004215 A1 6/2001 Kubota et al.
 2001/0021805 A1 9/2001 Blume et al.
 2002/0022777 A1 2/2002 Creighton, IV et al.
 2002/0055674 A1 5/2002 Ben-haim et al.
 2002/0058866 A1 5/2002 Segner et al.
 2002/0058884 A1 5/2002 Burbank et al.
 2002/0103430 A1 8/2002 Hastings et al.
 2002/0168618 A1 11/2002 Anderson et al.
 2002/0177765 A1 11/2002 Bowe et al.
 2003/0014044 A1 1/2003 Krishnan et al.
 2003/0036696 A1 2/2003 Willis et al.
 2003/0065271 A1 4/2003 Khoury
 2003/0082056 A1 5/2003 Ohya et al.
 2003/0114727 A1 6/2003 Wallace
 2003/0195433 A1 10/2003 Turovskly et al.
 2003/0205941 A1 11/2003 Suzuki et al.
 2003/0212373 A1 11/2003 Hall et al.
 2003/0233112 A1 12/2003 Alden et al.
 2004/0019447 A1 1/2004 Shachar
 2004/0054279 A1 3/2004 Hanley
 2004/0097805 A1 5/2004 Verard et al.
 2004/0097806 A1 5/2004 Hunter et al.
 2004/0097965 A1 5/2004 Gardeski et al.
 2004/0199074 A1 10/2004 Ritter et al.
 2004/0249262 A1 12/2004 Werp et al.
 2004/0249263 A1 12/2004 Creighton
 2004/0267156 A1 12/2004 Turovskly et al.
 2005/0004449 A1 1/2005 Mitschke et al.
 2005/0021078 A1 1/2005 Vleugels et al.
 2005/0096589 A1 5/2005 Shachar
 2005/0203375 A1 9/2005 Wills et al.
 2005/0222554 A1 10/2005 Wallace et al.
 2005/0256521 A1 11/2005 Kozel
 2006/0058663 A1 3/2006 Willis et al.
 2006/0095022 A1 5/2006 Moll et al.
 2006/0114088 A1 6/2006 Shachar
 2006/0116633 A1 6/2006 Shachar
 2006/0116634 A1 6/2006 Shachar
 2006/0150854 A1 7/2006 Benninger et al.
 2006/0217697 A1 9/2006 Lau et al.
 2006/0226713 A1 10/2006 Lehr et al.
 2006/0270903 A1 11/2006 Uchiyama et al.
 2006/0276775 A1 12/2006 Rosenberg et al.
 2007/0016006 A1 1/2007 Shachar
 2007/0016131 A1 1/2007 Munger et al.
 2007/0043338 A1 2/2007 Moll et al.
 2007/0062547 A1 3/2007 Pappone
 2007/0066880 A1 3/2007 Lee et al.
 2007/0083193 A1* 4/2007 Werneth A61B 5/0422
 606/41
 2007/0118215 A1 5/2007 Moaddeb
 2007/0197869 A1 8/2007 Uchiyama et al.
 2007/0197872 A1 8/2007 Uchiyama et al.
 2007/0197891 A1 8/2007 Shachar
 2008/0027313 A1 1/2008 Shachar
 2008/0039880 A1 2/2008 Nohilly et al.
 2008/0058656 A1 3/2008 Costello et al.
 2008/0091193 A1 4/2008 Kauphusman et al.
 2008/0177139 A1 7/2008 Courtney et al.
 2008/0230702 A1 9/2008 Rouso et al.

2008/0249395 A1 10/2008 Shachar et al.
 2008/0297287 A1 12/2008 Shachar et al.
 2009/0030411 A1 1/2009 Werneth et al.
 2009/0078571 A1 3/2009 Abarra et al.
 2009/0078875 A1 3/2009 Rouso et al.
 2009/0209950 A1 8/2009 Starksen
 2009/0231073 A1 9/2009 Horisaka et al.
 2009/0248014 A1 10/2009 Shachar et al.
 2009/0253985 A1 10/2009 Shachar et al.
 2009/0275828 A1 11/2009 Shachar et al.
 2010/0130854 A1 5/2010 Shachar et al.
 2010/0152590 A1 6/2010 Moore et al.
 2010/0256558 A1 10/2010 Olson et al.
 2010/0305402 A1 12/2010 Shachar et al.
 2010/0305429 A1 12/2010 Shachar et al.
 2011/0178532 A1 7/2011 Amiri et al.
 2011/0230896 A1 9/2011 Wallace et al.
 2011/0238083 A1 9/2011 Moll et al.
 2011/0301497 A1 12/2011 Shachar et al.
 2011/0319715 A1 12/2011 Uchiyama et al.

FOREIGN PATENT DOCUMENTS

EP 1 059 067 12/2000
 EP 1 115 327 7/2001
 GB 2367803 A 4/2002
 JP 2000-509316 7/2000
 JP 2001-448 1/2001
 JP 2001-509038 7/2001
 JP 2001-514040 9/2001
 WO WO 95-01757 A1 1/1995
 WO WO 97-29803 A1 8/1997
 WO WO 98-35720 A2 8/1998
 WO WO 99-11189 A1 3/1999
 WO WO 99-23934 A2 5/1999
 WO WO 00-76141 A1 2/2000
 WO WO 02-19908 A1 3/2002
 WO WO 02-34131 A1 5/2002
 WO WO 02-094115 A2 11/2002
 WO WO 02-094115 A3 11/2002
 WO WO 2004-006795 1/2004
 WO WO 2005-042053 A2 5/2005
 WO WO 2005-042053 A3 5/2005
 WO WO 2005-112813 A1 12/2005
 WO WO 2007-100559 A2 9/2007

OTHER PUBLICATIONS

Bergveld, Piet, "Development, Operation, and Application of the Ion-Sensitive Field-Effect Transistor as a Tool for Electrophysiology," IEEE Transactions on Biomedical Engineering, vol. BME-19, No. 5, Sep. 1972, 10 pages.
 Canadian Office Action for Application No. 2542863, dated Sep. 30, 2010.
 Extended European Search Report from 09005296.0, Aug. 19, 2009, 3 pages.
 Faddis et al., "Novel, Magnetically Guided Catheter for Endocardial Mapping and Radiofrequency Catheter Ablation," Journal of the American Heart Association, Nov. 11, 2002.
 Fink et al., "An Optically Switched PS-Radar for Pictorial Representation of Object Structures in Human Tissue," Experimentelle Technik Der Physik, vol. 38, No. 3, 1990, pp. 197-206, 10 pages.
 International Search Report for PCT/US2010/036149, dated Sep. 29, 2010.
 International Search Report for PCT/US2010/052684, dated Dec. 6, 2010.
 International Search Report for PCT/US2010/052696, dated Dec. 8, 2010.
 International Search Report from PCT/US03/22122, Nov. 6, 2003, 9 pages.
 International Search Report from PCT/US2007/004416, Aug. 24, 2007, 5 pages.
 International Search Report from PCT/US2008/056277, Nov. 18, 2008, 7 pages.
 International Search Report from PCT/US2008/060525, Oct. 31, 2008, 6 pages.

(56)

References Cited

OTHER PUBLICATIONS

International Search Report from PCT/US2009/039659, Jul. 6, 2009, 4 pages.

Ishiyama, K.; Sendoh, M.; Arai, K.I.; Magnetic micromachines for medical applications. *Journal of Magnetism and Magnetic Materials*. 2002; vol. 242; pp. 41-46.

Materials Library in FEMM 4.0, May 18, 2007, pp. 3-4.

Ritter, J.A.; Ebner, A.D.; Daniel, K.D.; Stewart, K.L.; Application of high gradient magnetic separation principles to magnetic drug targeting. *Journal of Magnetism and Magnetic Materials*. 2004; vol. 280; pp. 184-201.

Standard Specifications for Permanent Magnet Materials, Magnetic Materials Producers Association, 1964.

Supplementary Partial European Search Report from 04795885.5 Nov. 18, 2008, 5 pages.

Totsu, K.; Haga, Y.; Esashi, M.; Three-axis magneto-impedance effect sensor system for detecting position and orientation of catheter tip. *Sensors and Actuators*. 2004; Issue A 111; pp. 304-309.

* cited by examiner




Figure 1




Figure 2




Figure 3




Figure 4

SYSTEM AND METHOD FOR TARGETING CATHETER ELECTRODES

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a continuation of U.S. patent application Ser. No. 12/615,176, filed Nov. 9, 2009, the entirety of which is incorporated herein by reference and is to be considered part of this specification.

BACKGROUND

Field of the Invention

The invention relates to the systems and methods for guiding, steering and advancing an invasive medical device in a patient.

Description of the Related Art

In cardiac electrophysiological procedures, mapping catheters are used to define the geometry of a coronary chamber and map its surface electrocardiogram. Mapping catheters contain an array of electrodes which are used for position location and sensing the surface electrical activity. For sensing electrical activity, these electrodes are either used individually or in differential pairs, depending upon the type of sensory hardware available. When the surface has been fully mapped, a mapping catheter is often used in conjunction with an ablation catheter to locate and deliver therapeutic treatment at specific locations. The mapping catheter is returned to the area of interest, and the electrogram at each electrode or electrode pair is observed on the data recorder to determine the precise location along the mapping catheter for treatment. The ablation catheter is then guided independently to that location to deliver radiofrequency energy. Unfortunately, mapping of the heart chamber using prior art systems is a time-consuming process that increases the cost and risk of ablation procedures. The mapping process is complicated by the fact that the walls of a beating heart, not stationary, and the surgeon using traditional mapping catheters, does not have adequate control of the distal end of the catheter.

SUMMARY

The system and method described herein solve these and other problems by incorporating algorithms in a catheter guidance and control system that allows the operator to specify a target location as either a mapping catheter electrode, another location on the mapping catheter, or a mapping catheter electrode electrogram. The mapping process includes moving a catheter about a coronary chamber to define the average location of the walls and the electrical activity of the nerves within those walls during the heartbeat cycle.

The catheter guidance system then uses this live moving location to guide the therapeutic ablation catheter to this location or to tissue contact (e.g., where the tip of the catheter maintains relatively continuous contact with the surface of the heart chamber wall throughout the heartbeat cycle) near this location. This is done to increase the accuracy of targeting tissue contact at the location which is not possible with the targeting of a static geometric map. In one embodiment, the moving location corresponds to a Cartesian point on a geometric map which represents the average position of the tissue location that passes through that point.

In one embodiment, a spiral mapping catheter is manually positioned against the tissue surface. In one embodiment, a spiral mapping catheter includes a type of mapping catheter with a plurality of electrodes arranged along its coiled distal end. In one embodiment, the spiral mapping catheter can include five or more electrodes, ten or more electrodes, twenty or more electrodes, 50 or more electrodes, etc. In one embodiment, one or more of the electrodes involve a conductive ring on the catheter. The electrodes can be wired through the catheter line to the position detection and heart electrogram sensing hardware.

Manual controls are provided to adjust the amount of coil to make it larger or smaller, as well as to bend the assembly back and forth during the manual mapping process.

A magnetically-guided ablation catheter is introduced into the chamber to be used to deliver therapeutic energy. The ablation catheter can be used in an ablation procedure to apply energy (e.g., radio frequency electrical) to a specific location within the heart is to necrotize (kill) tissue and block neural conduction pathways as to eliminate electrical signals that are the cause of cardiac arrhythmias. In a magnetic guidance system, a magnet (either a permanent magnet and/or an electromagnet) is provided to the distal end of the catheter and the distal end is then guided into position by a system of electromagnets external to the patient.

The catheter guidance control and imaging system is given the location of the distal electrode of the spiral mapping catheter as the desired position for the distal tip of the ablation catheter. The catheter guidance control and imaging system moves the ablation catheter distal tip into contact with the distal electrode of the spiral catheter. As the spiral catheter electrode moves, the catheter guidance system adjusts the ablation catheter location to maintain contact with that electrode.

In one embodiment, the catheter guidance control and imaging system moves the catheter tip into contact with the distal electrode of the spiral catheter and then moves the distal tip of the catheter past the spiral catheter electrode until continuous contact is made between the catheter tip and the chamber wall.

In one embodiment, the operator selects the target electrode on the spiral catheter by positioning the mouse cursor over the electrode and double-clicking the left mouse button. The catheter guidance and control system continuously sends this electrode's live position as a target position for automatic guidance to automatically advance, steer and/or push a catheter toward a desired position.

In one embodiment, the operator selects the target electrode on the spiral catheter by positioning the mouse cursor over the electrode's electrogram trace and double-clicking the left mouse button. The associated electrode's live position is used as target for automatic guidance.

In one embodiment, the operator selects a target electrode pair on the spiral catheter by selecting the electrode pair's electrogram trace. The catheter guidance and control system continuously sends the average position of the electrode pair as the desired position.

In one embodiment, the operator selects a location between electrodes by positioning the mouse cursor over a location on the mapping catheter and double-clicking the mouse button. The catheter guidance and control system continuously sends an interpolated position between the adjacent electrode pairs as the desired position.

In one embodiment, the operator may target tissue contact on a specific side of a mapping catheter by selecting a side

3

preference cursor which appears when the mouse cursor is in close proximity to the mapping catheter.

In one embodiment, catheter guidance includes introducing a mapping catheter into a patient, moving the mapping catheter within the patient to bring an electrode provided to the mapping catheter in contact with tissues at various locations to generate a desired map, identifying a target location from the map and placing an electrode of the mapping catheter proximate to the target location, introducing a therapeutic catheter into the patient and guiding the therapeutic catheter to a location of the electrode. In one embodiment, the therapeutic catheter is moved past the location of the electrode. In one embodiment, the mapping catheter is guided using magnetic fields. In one embodiment, the therapeutic catheter is guided using magnetic fields.

One embodiment includes a system for catheter guidance having a mapping catheter having at least one electrode proximate to a distal end of the mapping catheter, therapeutic catheter, a first catheter guidance and control system that moves the mapping catheter to bring the at least one electrode in contact with tissues at various locations to generate a desired map, and a second catheter guidance and control system that moves a distal end portion of the therapeutic catheter to a location of the at least one electrode. In one embodiment, the therapeutic catheter includes an ablation catheter. In one embodiment, the second catheter guidance and control system includes a magnetic guidance and control system that uses a plurality of electromagnets to control a position of a magnet provided to a distal end of the therapeutic catheter. In one embodiment, the first catheter guidance and control system comprises a magnetic guidance and control system that uses a plurality of electromagnets to control a position of a magnet provided to a distal end of the mapping catheter. In one embodiment, the second catheter guidance and control system automatically moves a distal end portion of the therapeutic catheter to a location of the at least one electrode

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an illustration of an ablation catheter, spiral catheter and the catheter guidance and control elements.

FIG. 2 is an illustration of a set of catheter electrode electrogram traces.

FIG. 3 is an illustration of an ablation catheter in contact with a spiral catheter electrode.

FIG. 4 is an illustration of an ablation catheter tip moving beyond a spiral catheter electrode in order to acquire tissue contact near that electrode.

DETAILED DESCRIPTION

FIG. 1 shows a distal end of a spiral mapping catheter 4 and a distal end of an ablation catheter 1. The mapping catheter 4 includes a plurality of electrodes including an electrode 4.1 disposed at or near the distal end of the catheter 4, an electrode 4.2 disposed at a position on the catheter 4 less distal than the electrode 4.1, etc. The ablation catheter 1 is introduced into a coronary chamber via a sheath (or introducer) 2. The sheath (or introducer) 2 includes a tube which is inserted through a vein or other pathway or orifice into the heart. Catheters, wires and/or fluids can be introduced into the heart chamber through this tube.

In one embodiment, the tip of the ablation catheter 1 contains a magnetically-doped core element and sensory electrodes. The magnetic indicator 3 displays the current direction of the magnetic field that is guiding the catheter tip.

4

A spiral mapping catheter 4 is introduced into the chamber and manually guided by levers on its handle (e.g., at the proximal end, not shown) to a desired location. The operator uses a mouse cursor 5 to double-click on a representation of the distal electrode 4.1 of the spiral catheter 4 to command the catheter guidance control and imaging system to guide the ablation catheter 1 to the spiral catheter electrode 4.1. The operator may also select any location between locations, such as between the distal 4.1 and second electrode 4.2 and a linearly interpolated position will be sent to the catheter guidance control and imaging system.

FIG. 2 is an illustration of a set of catheter electrode electrogram traces 6. In one embodiment, the electrogram configured as a time versus amplitude plot of the electrical potential as measured at a specific point on, or in the body. Electrograms for each electrode pair can be displayed on the mapping system and/or on a separate ECG system.

Alternately to the process described in FIG. 1, the operator can use the mouse to double-click on a spiral mapping catheter's electrogram trace to command the catheter guidance, control and imaging system to guide the ablation catheter to that spiral catheter electrode or electrode pair. In this alternate embodiment, the operator selects the distal pair of spiral catheter electrodes 6.1 and the ablation catheter is guided to an average location between the distal electrode 4.1 and second electrode 4.2.

FIG. 3 shows the ablation catheter 1 in contact with a spiral catheter electrode where the ablation catheter 1 has been guided into contact with the spiral mapping catheter's distal electrode 4.1. The live electrode position of the catheter tip and the live electrode position of the distal spiral catheter electrode can be continuously synchronized by the catheter guidance and control system.

FIG. 4 shows the ablation catheter 1 moving beyond the spiral catheter electrode 4.1 in order to acquire tissue contact near that electrode. The operator has elected to automatically guide the ablation catheter 1 past the spiral catheter distal electrode 4.1 until tissue contact is made on the outside of the spiral catheter 4. The operator has used the side preference cursor 7 to select the side preference which moved the desired position that side of the spiral catheter electrode 4.1.

The words used in this specification to describe the invention and its various embodiments are to be understood not only in the sense of their commonly defined meanings, but to include by special definition in this specification structure, material or acts beyond the scope of the commonly defined meanings. Thus, if an element can be understood in the context of this specification as including more than one meaning, then its use in a claim must be understood as being generic to all possible meanings supported by the specification and by the word itself.

The claims are thus to be understood to include what is specifically illustrated and described above, what is conceptually equivalent, what can be obviously substituted and also what essentially incorporates the essential idea of the invention.

It is to be understood that the illustrated embodiment has been set forth only for the purposes of example and that it should not be taken as limiting the invention as defined by the following claims. For example, notwithstanding the fact that the elements of a claim are set forth below in a certain combination, it must be expressly understood that the invention includes other combinations of fewer, more or different elements, which are disclosed in above even when not initially claimed in such combinations. A teaching that two elements are combined in a claimed combination is further to be understood as also allowing for a claimed combination

5

in which the two elements are not combined with each other, but can be used alone or combined in other combinations. The excision of any disclosed element of the invention is explicitly contemplated as within the scope of the invention.

Insubstantial changes from the claimed subject matter as viewed by a person with ordinary skill in the art, now known or later devised, are expressly contemplated as being equivalently within the scope of the claims. Therefore, obvious substitutions now or later known to one with ordinary skill in the art are defined to be within the scope of the defined elements. Accordingly, the invention is limited only by the claims.

What is claimed is:

1. A method for catheter guidance in a heart, comprising:
 introducing a spiral mapping catheter into a patient, said mapping catheter further comprising a coiled distal end and a plurality of electrodes are arranged along said coiled distal end to form a conductive ring;
 moving said mapping catheter within the patient to bring one or more of said plurality of electrodes of said mapping catheter in contact with tissues in the heart at various locations to generate a desired map;
 identifying a target location from said map and placing one or more of said plurality of electrodes of said mapping catheter proximate to said target location;
 displaying at least one electrogram trace for said one or more of said plurality of electrodes;

6

receiving an input that selects said target location with a cursor placed on said at least one electrogram trace for said one or more plurality of electrodes;

synchronizing live electrode positions of the catheter tip and live electrode positions of the spiral catheter electrode;

automatically guiding an ablation catheter to the one or more of said plurality of electrodes of said mapping catheter proximate to said target location in response to the received said input; and

acquiring tissue contact between the tip of said ablation catheter and said target location by moving the tip of said ablation catheter past the one or more of said plurality of electrodes of said mapping catheter proximate to said target location.

2. The method of claim 1, further comprising bringing at least one pair of said plurality of electrodes of said mapping catheter in contact with tissues at various locations to generate said desired map.

3. The method of claim 2, wherein said at least one electrogram trace is for said at least one pair of said plurality of electrodes.

4. The method of claim 3, further comprising receiving said input that selects said target location with a cursor placed over said display of said electrogram trace for said at least one pair of said plurality of electrodes.

* * * * *